

## C110 DUCTILE IRON PUSH-ON FITTINGS

### C110 DUCTILE IRON PUSH-ON FITTINGS BASIC SPECIFICATIONS

- SIZES:**
- 4" - 24"
- MATERIAL:**
- Ductile Iron ASTM A536, Grade 65-45-12, 60-42-10 or 70-50-05.
- PRESSURE:**
- 350 PSI Water Working Pressure 4" - 24"
- TESTING:**
- In accordance with ANSI/AWWA C110/A21.10
  - In accordance with UL - FM requirements.
  - All fittings are hydrostatically tested in accordance with SIGMA Quality Management Standard.
  - All fittings are heat coded to ensure traceability and verification of metallurgical properties in accordance with SIGMA Quality Management Standards.
- LAYING LENGTH:**
- In accordance with ANSI/AWWA C110/A21.10.
- DEFLECTION:**
- Up to 5 degrees, in accordance with TYTON JOINT bell design.
- CEMENT LINING:**
- Double cement lined in accordance with ANSI/AWWA C104 / A21.4.
- COATING:**
- Interior of fitting is seal coated (asphaltic material) in accordance with ANSI AWWA C104/A21.4 and NSF61 approved.
  - Exterior of fitting is seal coated (asphaltic material) in accordance with ANSI/AWWA C110/A21.10 and NSF approved.
- GASKETS:**
- Dual hardness SBR in accordance with ANSI/AWWA C111/A21.11.
  - Also available in EPDM, NBR and CR.
- JOINT:**
- TYTON JOINT design
- APPROVALS:**
- 4"-16" Underwriters Laboratories listed and Factory Mutual Approved.
- STANDARDS:**
- Certified to NSF61 Standard including Annex G.
  - ANSI/AWWA C110/A21.10 for Full Body Ductile Iron Push-On Fittings for water and other liquids.
- INSTALLATION:**
- Per ANSI/AWWA C600 and C111 using DIP conforming to C150/C151 and PVC pipe conforming to C900/C905.